



Series 500 Pipe Railing

Series 500 Hand Rail System

Series 500 Pipe Railing



Series 550 Pipe Picket Railing with Double Top Rail System.

Series 550 Pipe Picket Railing with Double Top Rail System.

## Finishes

The clean contemporary design of Superior Aluminum Pipe Railing and Pipe Picket Railing, with your choice of ten decorative finishes, adds a distinctive touch to any building. Whether baked-on enamel, anodized or duranodic, these finishes are guaranteed to endure for years of continued service and maintenance-free beauty.



**TECHNICAL SUPPORT** - For continuous spans in excess of 40 feet, expansion joints should be provided. To make an expansion joint, one end of the spliced joint should not have structural adhesive applied so that it is free to move in or out of the pipe. If a joint is provided every 30 feet, the width of the gap should allow 1/8" expansion for each 40°F of expected temperature rise. All pipe railing splices should be made no more than 12" from the nearest post.

**MATERIALS** - All rails and posts shall be formed from extruded 6063-T6 aluminum of 1-1/2" Schedule 40 pipe size, except where there are formed elbows, whereby, 6063-T4 is used. All pickets are 3/4" round, formed from extruded 6063-T5 aluminum. All railing accessories shall be cast from ANSI 713 alloy. All fasteners used in the system shall be aluminum or stainless steel.

**WORKMANSHIP** - All pipe cuts shall be square and accurate for minimum joint-gap. Cuts shall be clean and free of chamfer, from deburring, nicks and burrs. Holes shall be drilled the proper size for a tight flush fit of rivets and screws. All posts grouted in concrete must have one 1/4" diameter weep hole, 1/2" above post collar, in the plane of the rail.

**RIGIDITY** - Post spacing shall not exceed 6' 0" center-to-center. All posts will be unspliced single pipe length. Lower rails shall be a single unspliced length between posts. All top rails shall be continuous whenever possible. All fasteners shall be tightened so that completed railing is rigid and free of play at joints and component attachments.

**SCOPE OF WORK**  
Superior Aluminum Series 500 railing meets federal safety requirements as determined by an independent testing laboratory. Test results available upon request.

## Consider the Advantages...

- No rusting - No painting
- Unlimited designs
- Easy installation without welding
- Durable and functional design
- Strong and decorative
- Saves on installation and maintenance labor

## ...and the Possibilities for: Contractors, Builders & Architects.

- Handicap Ramps
- Condominiums
- Industrial Buildings
- Stores
- Waste Water Treatment Plants
- Nursing Homes
- Municipal Buildings
- Schools
- Office Buildings
- Motels
- Churches
- Hospitals
- Factories
- Amusement Parks
- Restaurants
- Swimming Pools
- Cafeterias

# Non-Welded Aluminum Pipe Railing

## Strong, Durable and Maintenance-Free!

Meets OSHA, ADA and BOCA Safety Criteria

# SERIES 500



Non-Welded Aluminum

# SERIES 500 Pipe Railing



Series 500 Pipe Railing  
1-1/2" Dia. Post, Top Rail,  
Center Rail and Bottom Rail.

# SERIES 550 Pipe Picket Railing



Series 550 Pipe Picket Railing  
3/4" Dia. Pickets with 1-1/2" Dia.  
Post, Top Rail and Bottom Rail.

## Product Presentation


Superior Aluminum Non-welded Series 500 Pipe Railing and Series 550 Pipe Picket Railing are especially designed to utilize all the advantages of aluminum, where strength, durability and no-paint maintenance are key factors. Highest quality aluminum extrusions and castings are used with concealed fasteners, offering a smooth finish, making it the finest contemporary design available on the market today.

Components are easily assembled without welding by using mechanical fasteners at intersections and epoxy structural adhesive at splice joints.

Factory assembled (Series 500 or 550) railings are made to your exact specifications, resulting in further on-site fabrication savings. Special curves or pipe radius can easily be fabricated to fit your job. This makes for a practical sound investment for the budget-minded buyer.

Posts and top rails are assembled to run in continuous lengths. This results in a system that is stronger than one with a cast tee and cross connections, and it provides a continuous smooth top rail surface. The Series 550 pickets are factory assembled with a tight drive-in-fit to the top and bottom rails to assure squareness and rigidity. Preassembled sections up to 24 feet can be shipped factory-assembled or knocked down for reassembly.

Superior Aluminum Railings are available in standard heights of 32", 36", 42" or 48", and in custom heights upon request.




## Durable maintenance-free pipe railing which is quick and easy to install without welding.

Railing splices are designed for a tight press fit and must be compressed with a pliers to permit them to slip into the pipe. The areas to be joined should be cleaned thoroughly. Mix adhesive according to manufacturer's directions. Mix only enough that you can use within 1/2 hour. Apply adhesive to inside surface of pipe. Compress splice sleeve with a pliers, then slip into the pipe. Wipe off excess adhesive after components are properly joined. The areas connected together should be left undisturbed for eight hours, longer in cold weather.

## Tee Fittings




To attach the tee fitting to the post, a self tapping, stainless steel, hexagon head screw with lockwasher is positioned through the fitting and threaded into the 7/32" hole in the tubular post.



When two 90° tees are located directly opposite each other to form a cross, a stainless steel through bolt, lockwasher and nut are used.

## Mounting Options


Pipe or picket railing can be embedded in concrete and grouted, or mounted on decks and platforms with base flanges, or side-mounted on fascia or stringer by means of fascia flanges.




## Concealed Fasteners

## Part Applications

### Series 500 Pipe Railing




### Series 550 Pipe Picket Railing



Item	Description
502	Tee
503	Corner Tee
507	90° Three-Way Elbow
523	Heavy-duty Base with Post
521	Wall Plate with Adj. Brackets


Hand Rail System

## Picket Railing Design Selections




## Component Parts for Series 500 & 550


### No. 5B Picket




### No. 500 1-1/2" Schedule 40 Pipe -24'



### No. 501 Post (Any Type)




### No. 502 Tee (A)




### No. 503 Corner Tee (B)




### No. 504 Angle Tee (C)




### No. 505 Adj. Angle (0°-38°)




### No. 506 90° Miter Elbow




### No. 507 90° 3-Way Elbow (F)




### No. 508 Floor Flange (G)




### No. 509 Cover Flange (H)




### No. 510 90° Radius Elbow (I)




### No. 511 Bottom Step Post Elbow (J)




### No. 512 Top Step Post Elbow (K)



### No. 513 Rail Elbow (L)




### No. 514 Post Cap



### No. 515 Wall Bracket




### No. 517 Splice




### No. 518 Angle Flange with Post (M)




### No. 519 Wall Return Bend




### No. 520 Wall Plate with Brackets



### No. 521 Wall Plate With Adj. Brackets (N)




### No. 522 135° 3-Way Elbow




### No. 523 Heavy Duty Base with Post



### No. 540 Side Mount Flange



### No. 541 Heavy-Duty Base Welded to Post



### No. 550 Wedge Base with Stud

